



# QAM Snare Manager User Manual

---

QS-MUM-3.4

1/2/14

---

This document details the functions and operation of the QAM Snare Manager software package

## Table of Contents

---

<b>Overview .....</b>	<b>4</b>
<b>Software installation .....</b>	<b>5</b>
<b>Startup .....</b>	<b>6</b>
<b>Settings – System Settings .....</b>	<b>8</b>
<b>Server.....</b>	<b>8</b>
List of Hubs.....	8
List of PSID.....	10
Configuration.....	10
Email.....	11
CLI report.....	12
<b>Leak detectors .....</b>	<b>13</b>
List of devices .....	13
Global QAM channel configuration .....	13
FSK carrier.....	17
Device Calibration .....	17
Alarms .....	18
Alarms–GSM fault.....	18
Alarms–QAM detector fault .....	19
<b>Technicians .....</b>	<b>19</b>
List of technicians .....	19
Technician level .....	20
<b>Work order .....</b>	<b>21</b>
General configuration.....	21
Advanced configuration .....	22
Work order –priority assignment by band.....	22
Work order –priority assignment by technician level.....	22
Work order –priority assignment by geography .....	23
Close codes.....	24
<b>Manager .....</b>	<b>25</b>
Map .....	25
Driving route.....	25
Leak marker .....	26
User manager.....	26

<b>Settings – Hub Signals .....</b>	<b>27</b>
<b>Driving routes.....</b>	<b>27</b>
Calculate leak at point.....	30
Show motion path .....	30
Detection point leak characteristics .....	31
<b>Work Order / Database .....</b>	<b>31</b>
Structure of the database .....	32
Leak status definitions .....	32
Unassigned leak .....	32
Open leak .....	32
Closed leak .....	33
Calibrated leak .....	33
Show tech location .....	33
Google view –satellite.....	34
Remove leak from list.....	35
Remove group of leaks.....	35
Edit a work order – reassign to a different technician .....	36
Close a work order from Manager Program .....	36
Undo a previously closed leak .....	37
Calculate leak at point.....	37
Setup Calibrated leak .....	38
<b>File.....</b>	<b>38</b>
View downloaded driving routes.....	39
Simulate downloaded driving routes.....	39
Calibrated leak calculator .....	41
<b>Database .....</b>	<b>42</b>
Server audit.....	43
Load and show node boundary.....	44
Load and show PSID boundary.....	45
Edit Hub/Node boundaries .....	45
<b>Reports .....</b>	<b>48</b>
CLI report.....	48
Leak statistics .....	50
Driving route reports.....	53
Repair reports .....	55



Technicians productivity.....	58
Server Statistics.....	59
Device Calibration .....	60
Export Data.....	61
<b>Help .....</b>	<b>62</b>
Program help .....	62
Color indicator .....	63
About.....	63
<b>Print work order.....</b>	<b>63</b>

## Overview

---

QAM Snare technology detects digital leaks by performing a correlation process on a selected QAM channel. The correlation compares samples of the QAM channel from the cable network, with samples pulled off the air at the same frequency using an antenna. If there is correlation between the two signals, this indicates that the leakage detected off-air is the same signal as was carried on the network, and that it is with certainty a leak from the cable network.

For QAM Snare Monitor and Navigator, the samples of the QAM channel used for correlation originate at the headend, and are transmitted to the field unit via an IP connection. The QAM Snare Monitor and Navigator continuously correlate the signal set originating at the headend and the signal set pulled off of its local antenna, and when leakage is detected a database at the headend is updated with the relevant information and leak characteristics.

Simultaneous to the leakage detection, QAM Snare also tunes to LTE downlink and public safety frequencies and measures the LTE signal level at each detection point. This allows for intelligent prioritization of leak repair such that those leaks that likely will be most troublesome can be addressed first. This feature provides a huge benefit in the overall operating costs associates with leak mitigation.

QAM Snare Monitor is intended as a black box solution that continually performs leak detection without any driver or user involvement. It is intended to identify leaks and then store the leak data in the headend database, for future repair assignment.



QAM Snare Monitor can also be used for as a tool to identify and repair leaks if used in conjunction with some other tools. A companion piece, the QAM Snare Isolator, is a hand held unit designed for the last few feet device identification. It can be carried by the technician and brought up in the bucket in order to identify the exact device or connector that is the source of the leak. The QAM Snare Isolator operates in exactly the same fashion, but it receives the QAM channel samples in a different method. When QAM Snare Isolator pairs with Monitor, the Monitor changes its operational mode and functions as a data bridge such that samples from the headend are relayed to the Isolator. The Isolator then correlates the headend signal set with the signal set pulled from its local antenna. The wireless 900 MHz ISM band is used for communication between paired devices.

QAM Snare Navigator is intended as a tool for the user that is charged with actually fixing the leaks. As such it allows for the user to select the operating channel and the FSK frequency used to connect with Isolator as described above. It additionally has a display where leak characteristics, detected LTE signal level, and a map showing leak location can be viewed. It can automatically receive work orders, and it has the ability to close leaks directly from the device.

Additionally, the QAM Snare Web Client, run from a web browser on either a PC or a mobile device, can display work orders and display the leak location on a Google map such that the user can get to the offending location, perform the repair, and close out the work order.

## Software installation


---

Install the current version of the QAM Snare Manager executable program downloaded from the Arcom FTP or web site [www.arcomlabs.com](http://www.arcomlabs.com).






Then install the executable map file for the desired state/location. Files are copied to the appropriate direction and no further user interaction is required.




To start the QAM Snare Admin, click the QAM Snare Admin icon.



## Startup


---

First, press the Connect to Server button.




The Server Manager appears. If Server is already loaded simply press the desired hub, in the case below syr 22 and enter password, or for a new Server press the new Server button indicated by the red arrow below. To edit an existing Server, press the

edit button indicated by the blue arrow below. To delete a Server press the red X delete button.



As shown below, enter the Server name and IP address in the box where localhost is currently written. If a cloud server is being utilized, enter the complete server Dynamic DNS domain name.




Press ok, then highlight the selected Server and enter sign in credentials.

The program will start by loading the installed state maps. This will take a few moments depending upon the speed of the PC. The software may be used during this initial map loading period.




Each time you enter the program, as the map is loading it will show a progress bar at the bottom of the screen. The map for each state contains overlaps onto adjacent states, so regions close to a border are not a problem.



## Settings – System Settings

The System setting menu item controls all aspects of how the system is configured, how alarms are generated, and establishes which QAM channel and FSK various connected devices operate on. To access System setting, click on the menu item.




There are several major categories within System settings: Server, Leak detectors, Technician, Work order, and Admin.

## Server

### List of Hubs


QAM Snare is designed to operate in multi-hub environments, where devices installed in vehicles roam freely between hub boundaries. The GPS hub boundaries are loaded into the headend servers such that each device always receives samples from the correct headend, ensuring

proper leak detection. The list of Hubs provide information as to the connected hubs. If there is only one hub it is listed as a Local hub as shown below. When properly communicating, Status should be displayed as OK.






Press the Add button to add a new hub to connect with the Server.



Then enter the Hub name, Hub IP (or Dynamic DNS), and CLI report number and number of Plant miles.

A Windows-style dialog box titled 'New Hub'. It has a title bar with a minus, maximize, and close button. The dialog contains four text input fields: 'Hub Name:', 'Hub IP:', 'CLI report #:', and 'Plant miles:'. At the bottom right, there are 'OK' and 'Cancel' buttons.

Press the Edit button to edit information about an existing hub.



Enter the updated information and press OK.


A Windows-style dialog box titled 'Edit Hub info'. It has a title bar with a minus, maximize, and close button. The dialog contains four text input fields with pre-filled values: 'Hub Name:' (hub136), 'Hub IP:' (192.168.1.136), 'CLI report #:' (12), and 'Plant miles:' (7). At the bottom right, there are 'OK' and 'Cancel' buttons.

To delete an existing hub press the Delete button.



Delete

And confirm the action by answering yes when prompted.





## List of PSID

QAM Snare has the ability to display Physical System Identification (PSID) boundaries. The list of PSID shows all numbers associated with the server.

The PSID boundaries are entered by Arcom Digital as an administrative function based upon information provided by the system.

If desired, comments regarding each PSID can be added to each line item by clicking on the highlighted line.



## Configuration

QAM Snare is designed to allow for field unit to collect leak data within multiple frequency bands – and to provide summary reports on leakage at various frequencies within these bands. The frequency bands are low (aeronautic), middle (HD broadcast), and high (LTE) – for consistency between various reports and other system output,



these frequency bands are fixed and can't be changed by a user. The lower frequency limit of QAM Snare is fixed at channel 16, and the upper frequency is 195MHz. Middle band starts at 201MHz and ends at 645MHz. And the high LTE band starts at 651MHz and ends at 885MHz.

Within the configuration settings, options are provided to not update detected leaks to the database after the vehicle has been stationary for a certain period of time. This is for scenarios where there is not leak at a location and a technician goes to fix something else.


This prevents a leak from being recorded when the technician performs an action such as opening an amplifier. The time setting provides a way to change the amount of time after which no leak has been recorded, that the database is locked from being updated. This menu item also allows for enabling email notification to be automatically sent to the technician nearest a large leak. The last menu item provides a method to limit the number of simultaneous users connecting with QAM Snare Manager to the Server.

## Email

SMTP alarms can be configured under the Email menu item. Information on your SMTP server that is used to forward the alarms is entered here. This information should be able to be supplied by your IT department. Select the Use Amazon cloud server option for SMTP if you want to use a hosted SMTP service.

## CLI report

QAM Snare Manager provides the ability to automatically generate the FCC form 320. This section is used for setup information, the actual report is generated through the Reports tab.



System settings

CLI report - FCC form 320

Section I | Section II | Section III | Section IV

System owner:

Address:

City:

State:  Zip code:


Phone:

Community served:

Community ID:

Physical system ID:

Apply Close



System settings

CLI report - FCC form 320

Section I | Section II | Section III | Section IV

Responsible person:

Address:

City:

State:  Zip code:


Phone:

Test result type: ☒ CLI infinity ☐ CLI 3000

Center of the cable system:

Latitude:  Longitude:

Apply Close



System settings

CLI report - FCC form 320

Section I | Section II | Section III | Section IV

Test person:

Phone:

Total plan miles:  0.0


Equipment make:

Equipment model:

Test frequency:  0.0

Exhibit B ref. no.:  0

Apply Close



System settings

CLI report - FCC form 320

Section I | Section II | Section III | Section IV


Official title:

Apply Close

## Leak detectors

### List of devices

The List of devices table provides information on all Navigators and Monitors that have connected to the hub. Current status is indicated as either on-line or off-line. This status refers to whether or not the device is actively communicating with the hub – it does not indicate




The screenshot shows the 'System settings' window with the 'List of devices' tab selected. The table lists 11 devices, all of which are 'Navigator' type and 'offline' status. The columns are: #, Device type, Device ID, Technician ID, Calibrated, Status, and Alarms.

#	Device type	Device ID	Technician ID	Calibrated	Status	Alarms
1	Navigator	Arcomb	Arcomb	7/3/2013	offline	-
2	Navigator	Arcom	Arcom	11/8/2013	offline	-
3	Navigator	TEMPTESTS	ddeyo	8/15/2013	offline	-
4	Navigator	Rob	4426	8/15/2013	offline	-
5	Navigator	00069	G	8/20/2013	offline	-
6	Navigator	00040	G	8/21/2013	offline	-
7	Navigator	00318	ArcomSB	8/23/2013	offline	-
8	Navigator	Rev07	G	8/29/2013	offline	-
9	Navigator	c1m	22222	9/5/2013	offline	-
10	Navigator	00684	Arcom	9/8/2013	offline	-
11	Navigator	00675	Arcom	9/8/2013	offline	-

any alarm condition such as no GPS or no wireless. Information on these alarms is indicated in the Alarm column. The alarm conditions are defined and established in the Alarm section this Leak detector settings menu item.

Using the Edit and Delete buttons, devices can be deleted from the listing or information on the technician ID assigned the device can be edited. Device type and Device ID are configured on the Navigator and Monitor, and cannot be changed. If a user does change the Device ID on a unit, the next time it connects it will register with the new Device ID, and it would be a good idea to delete the old from the List of devices.



The 'Edit technician' dialog box shows the 'Technician information' section. It contains fields for Device type, Device ID, Technician ID, and Comments. The values are: Device type: Monitor, Device ID: SYR\_Mon\_1, Technician ID: Edward Jones, and Comments: (empty). There are OK and Cancel buttons at the bottom.

Technician information	
Device type:	Monitor
Device ID:	SYR_Mon_1
Technician ID:	Edward Jones
Comments:	
Comments, additional information of the technician. Can be empty.	
<div>OK</div> <div>Cancel</div>	

### Global QAM channel configuration

Since QAM Snare can simultaneously process four channels, and since there will likely be many devices in the field that could potentially request more than the four



channels that the Server and Headend Signal Processors can provide – to avoid conflict some controls were necessary.

QAM Snare Monitor was designed primarily to be used passively with no driver/technician involvement. Typically one or two channels will be selected for high and low frequency leak monitoring, and the units will drive around passively acquiring data – to be fixed at a later time. QAM Snare Monitor is configured using the Q-browser software over a USB interface. Configuration parameters are IP address of the headend, information related to the GSM connection, and FSK parameters. The QAM channel is configured and controlled via the QAM Snare Manager program – the purpose being to ensure that there are no conflicts in more than four channels being requested, and to make it easy to switch frequencies on a fleet of vehicles, without necessity of going to each unit individually. QAM Snare Navigator works a little differently. Since it is designed to be used by line technicians to repair problems, and since it has an easy to use user interface – switching of QAM channels by the user is allowed – within certain parameters that prevent conflict. These parameters are again controlled through the QAM Snare Manager program and are explained below.

Within the Admin, in System Settings – there is the ability to configure the system in four ways:


1 – No global QAM Channels configured – This setup would only be possible if no Monitors are used in the system, because setting at least one global QAM channel is required in order to use Monitor. In this configuration, The first four Navigators that connect to four different frequencies, reserve those frequencies until all users disconnect. As an example, assume four Navigators are operating at four different frequencies. If a fifth Navigator tries to connect at a fifth frequency, an error message would pop up on the screen of the fifth Navigator telling the user which four frequencies are available. This fifth user would have to use either of the four specified frequencies. If say the second user disconnected (assuming previously a fifth user didn't also connect to that channel), a frequency would then become open, and the fifth user could then connect to any channel. But obviously if the second user again tried to connect, he would be limited to the frequencies established by the other units. So it is easy to see that in a situation with many users all trying to do something different, that this configuration could be somewhat confusing and possibly frustrating.

2 – One global QAM Channel configured – This is a minimum required if any Monitors are used in the system. Here, all the Monitors in the system would have to operate on the one global channel specified. Navigators could tune to that channel, or any of the other three.

3 – Two global QAM Channels configured – This is required if a system wants to simultaneously use Monitors configured to different frequencies. In the Manager program the two channels are selected and the Manager program assigns which Monitor devices are set to which frequency. Navigators can select the global channels or as a group any of two other frequencies.

4 – Three QAM Channels configured – This is required if a system wants to simultaneously use Monitors configured to three frequencies. Navigators can select the global channels or as a group one other frequencies.

Global QAM channels are configured on the page to the right. From this menu item an Administrator can change either of the configured QAM channels, or clear a channel from



The screenshot shows the 'System settings' window with the 'Global QAM channel configuration' tab selected. The left sidebar lists various system settings, with 'Global QAM channel configuration' highlighted. The main panel displays the following configuration:

- TV standard: NTSC
- QAM channel #1: 83/579.0MHz (with a 'Clear default frequency' link)
- QAM channel #2: 88/609.0MHz (with a 'Clear default frequency' link)
- QAM channel #3: 113/729.0MHz (with a 'Clear default frequency' link)

Below the channel configuration is a table titled 'QAM channel to Monitor device associations'.

#	Device ID	Technician ID	QAM channel #
1	SYR_Mon_1	SYR_Mon_1	1
2	QSnareBlackBox2	TechID2	1
3	ArcomTestM	ArcomTestM	1
4	ArcomTesto	ArcomTesto	1
5	QSnareBlackBox	TechID	1


At the bottom right of the window are 'Apply' and 'Close' buttons.

being a default. Additionally, there is a table that allows Monitor devices to be assigned to operate on either of the two QAM channels.


When selecting to clear or change a QAM channel, since any current users will be




disconnected, warning messages appear that let the program user know that the changes will be made globally.



When multiple changes are made, different choices can be selected and the **Apply** button allows all parameters to be changed simultaneously.




To change or to assign a frequency to a newly connected Monitor, highlight the desired device in the table and hit enter, and then select either default channel 1 or 2 from the dropdown menu. And click OK when finished.




## FSK carrier

The current settings for FSK carriers for all devices are displayed in this menu item. FSK for the Navigator is established by local device settings, and cannot be changed through the Manager program. It is listed for information purposes only. For Monitors, FSK is initially configured as part of the device setup through the Q-browser program – but it can be overridden by making changes through the Manager program. The FSK setting in the Manager program has higher priority than any FSK settings made locally through the Q-browser, so after initial connection with the hub the FSK for Monitors can only be changed through this Manager program.



#	Device type	Device ID	Technician ID	FSK freq., MHz
9	Navigator	GCI	GCI	915.00
10	Navigator	PALNL	PALNL	915.00
11	Navigator	QAMB	QAMB	915.00
12	Navigator	ArcomTest3	ArcomTest3	915.00
13	Monitor	SYR_Mon_1	SYR_Mon_1	926.00
14	Monitor	QSnareBlackBox2	TechID2	921.00
15	Monitor	ArcomTestM	ArcomTestM	914.00
16	Monitor	ArcomTesto	ArcomTesto	922.05
17	Monitor	QSnareBlackBox	TechID	926.00
18	Monitor	ArcomTest8	ArcomTest8	914.00
19	Monitor	QSnareBlackBoxADR	TechID	926.00
20	Monitor	QSnare_Mon_ADR	QSnare_Mon_ADR	926.00


To edit the FSK for a Device, click on that device, change the FSK from the pulldown menu, then press ok. *You are only able to change Monitor devices (highlighted with shading to distinguish) – you will not be able to change Navigator devices (rows shown with a white background).*



Monitor parameters	
Device ID:	QSnareBlackBox
Technician ID:	TechID
FSK frequency, MHz:	926.00
QAM channel #:	1
<div>OK Cancel</div>	

## Device Calibration


QAM Snare Manager contains a built in system to ensure that devices are calibrated at a calibrated leak location within a desired period of time. Changes to



Device calibration	
Setup device calibration	
Period of time (month 1..12):	6
<div>Apply Close</div>	

the calibration time period is configured here.

## Alarms



Alarms are designed to provide feedback to managers and users when a Monitor device is not functioning properly for a period of time that corresponds to the work day. Alarms can be seen on either the Manager program under List of devices, or by using the

web client. To cut down on unnecessary alarms and to provide a real indication of performance during the time the device is expected to be operational, an alarm scheduler is provided, such that alarm reporting only occurs during work days between working hours. To configure this feature, click on the day of the week to select and unselect, and then enter the hours for a typical work day. The time duration prior to generating an alarm during the work period can be selected for the two types of alarms, GSM fault and QAM detector fault. To disable this alarm feature configure the work day to not exist (i.e. working time is from 1 hour to 1 hour).

### Alarms-GSM fault

A GSM fault is the generic name for the condition when the server does not receive any communication from the Monitor within the constraints of the configured work day and alarm period. The cause may be lack of power to the device (vehicle turned off), lack of wireless access point, lack of GSM or WiFi antenna, wrong server configuration, etc. Configuration is recommended to be beyond the typical time interval for a service call or lunch break period.

## Alarms–QAM detector fault

The QAM detector fault alarms under the condition of no leaks being detected by the Monitor within the constraints of the configured work day and alarm period. To avoid false alarms configuration is also recommended to be beyond the typical time interval for a service call or lunch break period, or the interval that it is expected that a leak should be detected.

## Technicians

### List of technicians

Information on technician assigned to various QAM Snare devices, and those that may be assigned work orders is maintained here. Whenever a QAM Snare Navigator or Monitor connects to a hub, it will automatically appear in this listing. At that point, information pertaining to the technician assigned to that particular device may be added. Scroll to the right to add more detailed information for each technician. If desired, color coding can be used when showing the drive route for each technician, such that when multiple drive routes are displayed in the Show Motion Path mode – each individual technician can be easily identified.

System settings

Server

- List of Hubs
- Configuration
- E-Mail
- CLI report

Leak detectors

- List of devices
- Global QAM channel configuration
- FSK carrier
- Alarms

Technicians

- List of technicians
- Technician level

Work order

- General configuration
- Advanced configuration
- Close codes

Admin

**List of technicians**

+ Add    Edit    Delete

#	Name	Tech ID	Departm.	Level	C
1		ArcomTest		line tech High	N
2		ArcomTest		line tech Low	N
3		qs2014No1			N
4		qs2014No2			N
5		qs2015No2			N
6	Joe Smith	qs2015No1		Installer	N
7		qs2016No2			N
8		ArcomTest7121		Installer	N
9		GCLI		Installer	N
10		PAI NI		Installer	N

Apply    Close

**List of technicians**


+ Add    Edit    Delete

Phone	Address	Comments	Color
		Web+	

Click the edit button to edit information on a technician, this method is also used to enable Web access.

Click the Add button to Add a new technician. If a technician is added in this fashion, he is always assigned as having a QAM Snare Isolator.

Clicking on the Motion path color opens a pallet, such that a color can be assigned to the technician. Press OK to confirm.




**Edit technician**

**Technician information - BS-1**

Technician name:	Bruce
Technician ID:	BS-1
Department:	
Level:	
E-Mail:	bruce@cableco.com
Phone:	
Address:	
Comments:	
Enable web access:	<input type="checkbox"/>
Access password:	
Motion path color:	<span style="background-color: cyan; border: 1px solid black; padding: 2px;"> </span>
Confirm password:	

Email address of the technician. Can be empty.

OK Cancel



**Color**

Basic colors:


<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span>
<span style="background-color: red; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: yellow; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: green; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: cyan; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: blue; width: 15px; height: 15px; display: inline-block;"></span>	<span style="background-color: magenta; width: 15px; height: 15px; display: inline-block;"></span> </

## Work order

QAM Snare contains a built in work order system that can automatically assign leaks to be repaired by technicians. The way in which work orders are assigned is configured in the Work order General configuration tab and in the Advanced configuration tab. Additionally, work order close codes can be edited in the Closed code tab. Along with information about the device and technician, it shows whether or not a Technician has been assigned to automatically receive work orders, and how many work orders per day are assigned. Leak thresholds above which leaks are assigned is also indicated here, as well as the Work order time, which specifies the time of day when the next group of work orders are assigned.

## General configuration

In the General configuration tab the threshold leak level above which work orders are automatically assigned is defined. This threshold level can be set to different values for each of the three



**System settings**

**Work Order general settings**

Thresholds to generate Work Order

Low (Aeronautic) frequency band: Leak level [ $\mu\text{V/m}$ ]: > 21

Middle (HD broadcast) frequency band: Leak level [ $\mu\text{V/m}$ ]: > 25

High (LTE) frequency band: Leak level [ $\mu\text{V/m}$ ]: > 30

Work order daily reset time

1:00:00 AM


List of technicians assigned to Work Order

#	Technician ID	Device type	Assigned	WO number
2	ArcomTest	Navigator	+	5
3	qs2014No1	Navigator	+	3
4	qs2014No2	Navigator		

Apply Close

frequency bands (aeronautic, HD broadcast, and LTE). Work order daily reset time is defined as the time of each day when the assign work order process task is performed. The List of technicians assigned to work orders establishes which technicians are given work orders, and how many per day they are given.

In the table above, the presence of the + symbol shows that only technician # 2 and 3 on the list are assigned work



**System settings**

**Work Order general settings**

Work order parameters

Assigned: ☒

Work orders number: 5

OK Cancel

#	Technician ID	Device type	Assigned	WO number
1	ArcomTest	Navigator	+	5
2	ArcomTest	Navigator	+	5
3	qs2014No1	Navigator	+	3

Apply Close



orders, and in the case shows #2 is assigned 5 and #3 is assigned 3. To change this, click on the technician ID – and the Work order parameter box will appear. Simply check the box if this technician is to be assigned work orders and change the quantity per day with the up/down arrows.

Previous work orders need to be closed before new work orders are assigned. For example, if a technician is assigned 5 as the number of work orders he is given – if only one was closed during the day, then on the subsequent day only one additional work order will be assigned. If all 5 were closed, then 5 new would be assigned. A maximum of 10 work orders can be assigned to each technician each day.

### Advanced configuration


---

Advanced work order configuration allows for work orders to be assigned on a priority basis for certain high level leaks and importantly for detected LTE signal level. It additionally allows assignment by technician level and assignment based on geography.

### Work order –priority assignment by band

---

As shown below, selecting this option puts work orders that meet this criterion at the top of the list to be assigned. Leaks can be priority assigned for different defined amplitudes within each of the three leak bands, and importantly can also be assigned based upon detected LTE signal level. LTE signal level provide a very useful indication as to the potential for a particular leak to be the source of an LTE problem.




### Work order –priority assignment by technician level

---


If desired, leaks can be assigned to a certain level technician based on the characteristics of the leak. For example, LTE leaks are predominantly hard line problems – which should go to line techs. Low frequency leaks are typically soft cable which would be assigned to fulfillment techs. So each

of the three frequency bands can have leaks assigned to certain types or levels of technicians, or alternatively any large level leak detected, regardless of band – can be assigned to a certain level technician. The listing of technician and level can be customized in System settings – Technicians – List of technicians & Technician level.



### Work order –priority assignment by geography


Work orders can also be assigned based on geographical features such as the detected leaks being in close physical proximity to each other. This makes for cost effective and efficient drive time. In the box below simply check the box and select the proximity distance.



Work order can also be assigned based upon hubs and nodes that are assigned to various technicians. Check the box for this category and then press the edit button to configure. The screen below will appear. A listing of all hubs attached to the master is

shown on the X axis, and on the Y axis is a listing of the technician ID's that are assigned to a QAM Snare device. If the technician ID is not set up to receive work orders, then his name is crossed out. To enable, go into system Settings – Technicians, and allow work orders for that technician.

To make changes to assigned nodes and hubs, click on the white grid space that corresponds to the desired technician and hub. A listing of all nodes in that hub will appear as is shown below. Click on as many as desired, or right click to select all or clear all. Statistics on the number of assigned nodes are shown on the bottom row.



Technician ID	Hub ID	Local hub	ADR	vzinevich	bad	Hubs	Nodes
qe2014No2	4					1	4
qe2015No2							
qe2015No1							
qe2016No2							
SYR_Mon_1							
ArcomTest7121							
ArcomTestM							
ArcomTesto							
GCli	3	8	8			3	19
ArcomTest8							
PALNL							
QAMb							
ArcomTest3							
<b>Total % of assigned nodes</b>		<b>36.2%</b>	<b>100.0%</b>	<b>100.0%</b>	<b>100.0%</b>		


  

**Nodes assigned at Hub: Local hub, for tech ID: ArcomTestM**

<input type="checkbox"/> 137	<input type="checkbox"/> 28	<input type="checkbox"/> 3116
<input type="checkbox"/> 138	<input type="checkbox"/> 29	<input type="checkbox"/> 3117
<input type="checkbox"/> 139	<input type="checkbox"/> 30	<input type="checkbox"/> 3118
<input type="checkbox"/> 145	<input type="checkbox"/> 3054	<input type="checkbox"/> 3119
<input type="checkbox"/> 146	<input type="checkbox"/> 3058	<input type="checkbox"/> 3154
<input type="checkbox"/> 147	<input type="checkbox"/> 3060	<input type="checkbox"/> 3155
<input type="checkbox"/> 148	<input type="checkbox"/> 3069	<input type="checkbox"/> 3156
<input type="checkbox"/> 149	<input type="checkbox"/> 3070	<input type="checkbox"/> 3157
<input type="checkbox"/> 150	<input type="checkbox"/> 3071	<input type="checkbox"/> 3158
<input type="checkbox"/> 151	<input type="checkbox"/> 3072	<input type="checkbox"/> 3159
<input type="checkbox"/> 152	<input type="checkbox"/> 3073	<input type="checkbox"/> 3160
<input type="checkbox"/> 2427	<input type="checkbox"/> 3074	<input type="checkbox"/> 3161
<input type="checkbox"/> 2428	<input type="checkbox"/> 3088	<input type="checkbox"/> 3192
<input type="checkbox"/> 2429	<input type="checkbox"/> 3089	<input type="checkbox"/> 3193
<input type="checkbox"/> 2430	<input type="checkbox"/> 3091	<input type="checkbox"/> 3194
<input type="checkbox"/> 27	<input type="checkbox"/> 31	

## Close codes

It is often desirable to track and look at statistics related to the cause of leaks and physical impairments in the plant. As such a close code list is provided. This list is editable by any Manager program user, line items can be changed, deleted, or added. The complete close codes list is transmitted to each QAM Snare Navigator as part of its startup procedure, so its code listing is always current. Other than this Manager program, the



Code	Description
1	Unknown problem
2	Defective Drop
3	Defective Drop Splice
4	Defective Drop Connector
5	Defective Drop Passive
6	Unauthorized Equipment
7	Defective Inside Wire
8	Defective Inside Equipment
9	Defective Feeder Cable
10	Defective Passive Device
11	Defective Feeder Connector
12	Defective UG Drop


other method to enter close codes is through the web client, which uses this same database as its close code source.

## Manager

These settings establish how maps and leaks are displayed locally when viewed using the Manager program. These settings do not change how data is stored in the database. Through the user manager password and user ID access to the Manager program can be controlled.


## Map

This changes various items displayed on the maps. Node, Hub, and PSID boundary colors and line styles can be changed by clicking on the color or selecting from drop down. These changes only affect how the information is shown on the users software and is not changed globally. Click Apply to accept changes.



## Driving route


This allows the user to change the drive route marker indications based upon recorded leak level. If for example you want to ignore all leaks below a certain threshold,



simply adjust the setting accordingly. Motion path width changes the size of the marker when displaying a drive route in the Show Motion Path mode.



## Leak marker

This allows for different color flags to be displayed depending upon leak magnitude. Simply adjust the leak magnitude up or down based on how you want to display. The shape of the displayed marker can also be selected.





## User manager

The user manager setting allows an administrator to grant access to other users to this Admin program. It also provides a mechanism for users to change their own password.




## Settings – Hub Signals

The hub settings menu item allows the user to look at actual signals being sampled at the headend signal processor. First select the hub you want to look at from the pull down menu at the upper right. If there is only one hub installed it will show as Local hub. Click on Get GPS data to see if GPS is locked and operating properly. It is critical that the GPS setting indicate A/A to ensure GPS is locked.



## Driving routes





To view driving routes for individual Navigators and Monitors that are stored in the QAM Snare database, select this item. In the selection box, pick the Device ID you would like to view, select a range of route dates to pick from. Then click on button #3, Get driving route list.

The screenshot shows the 'Stored driving route manager' window. It has five numbered steps:

- 1. Device ID (Technician ID)**: A list box containing 'ArcomTest (Arcomtest)', 'ArcomTest2 (Arcomtest2)', 'ArcomTest3 (Arcomtest3)', 'COX2 (COX2)', and 'COX1 (COX1)'. 'COX2 (COX2)' is highlighted.
- 2. Select driving route dates**: Two date pickers. 'From:' is set to '4/20/2012' and 'To:' is set to '4/20/2012'.
- 3. Get driving route list**: A button.
- 4. Check driving routes to download**: A table with columns: Device ID, Technician ID, Points, Leaks, Distance, File ID, and Size. The table is currently empty.
- 5. Load and show driving routes**: A button.


A 'Cancel' button is located at the bottom right.

A listing of routes is shown, click on the desired route or routes, and then press the next button #5. The full route will appear.


The screenshot shows the 'Stored driving route manager' window after clicking 'Get driving route list'. The results are displayed in the table under step 4:

	Device ID	Technician ID	Points	Leaks	Distance	File ID	Size
<input checked="" type="checkbox"/>	COX2	COX2	9210	21	14.3 ml	19-04-2012.padr	322350
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							
<input type="checkbox"/>							

The 'Device ID' list box in step 1 still shows 'COX2 (COX2)' highlighted. The 'From:' date is now '4/19/2012' and 'To:' is '4/20/2012'. The table title is '4. Check driving routes to download [COX2]'. The 'Load and show driving routes' button is now active.




To view detailed information on a leak, right click on the flag and information about the detected leak, including a circle showing the leak radius will appear. In the example to the left, the leak was detected only at 729MHz, and the other frequencies are shown as blank. To get additional information on the detected time delay, press CTRL as you click on the leak.




## Calculate leak at point

The software contains a useful utility that has the ability to show the leak level at any location. Move the mouse to any location on the map and right click, then select Calculate leak at point. An information box appears that shows the leak level at the desired location, that is resultant from the existing leaks in the database. The three lines of information correspond to the three configured detection bands. In the example to the right leakage was only being monitored at the high frequency band.




## Show motion path

Clicking on Show motion path provide for an easier to view color coded line of the drive path. The color coding and line weight can be customized under System Settings, List of Technicians.





## Detection point leak characteristics

Left clicking on any alarm point provides details on the detected level and frequency for that data point.



## Work Order / Database

The Work Order / Database button gets you back to the default startup screen. This would be used for example, after you view a drive route and want to get back to the main database.





## Structure of the database

The QAM Snare database contains a significant amount of information. For each detected leak information on leak level, detected channel, detected LTE signal level, GPS coordinates of leak, radius of potential location, technician ID that detected the leak, QAM channel it was detected on, hub ID, status of the leak, close code, etc. By selecting different options from the pulldown menu below, leaks can be displayed in a variety of ways to suit user preference.

Order/leak type:	Technician ID:	From:	To:	Leak level >=:	QAM band/channel:	Hub ID:	<input type="checkbox"/> Show tech location	<input type="checkbox"/> Load and show node boundary
All	All	11/ 8/2013	11/ 8/2013	All	All	All		

## Leak status definitions

Each detected leak has a status related to what was done with the leak relative to work orders.

Order/leak type:
All
Unassigned
Open
Closed
Calibrated

## Unassigned leak

An unassigned leak is any leak that has not yet been assigned a work order for repair.


## Open leak

An open leak is any leak that has been assigned a work order to be repaired, but repair has not yet been completed.

Order/leak type: Technician ID:		From:	To:	Leak level >=:	LTE level >=:	QAM band/channel:	Hub ID:	<input type="checkbox"/> Show tech location		
<div>Open</div>	<div>All</div>	<div>12/ 4/2013</div>	<div>12/ 4/2013</div>	<div>All</div>	<div>All</div>	<div>All</div>	<div>All</div>	<div></div>		
Leakage table - open leaks [5 total]										
Leak ID	Detected date	Repaired dat...		Leak level [µV/m]	LTE level [dBm]	Address	PSID	Hub	Node	Repaired date
		Date	Tech ID							
181	9/17/2013	12/4/2013	Ggsm2	794	-60	287 Ainsley Dr, Syracuse		syracuse2		
197	11/20/2013	12/4/2013	Ggsm2	447		148 Game Rd, Syracuse		syracuse2		
182	9/17/2013	12/4/2013	Ggsm2	355		Ainsley Dr, Syracuse		syracuse2		
205	12/3/2013	12/4/2013	Ggsm2	282	-89	287 Ainsley Dr, Syracuse		syracuse2		
185	9/17/2013	12/4/2013	Ggsm2	40	-66	349 Ainsley Dr, Syracuse		syracuse2		


## Closed leak

A close leak is a leak that was assigned a work order, where the work order was completed and status changed to closed. When displayed on a map, closed leaks are always displayed with blue flags (unless color was changed). Additionally, closed leaks also contain information as to when they were closed, which technician performed the close process, and close code information as to the cause of the problem as well as the level of the leak post fix. Leaks can be closed through the Manager program, the web client, or directly from a QAM Snare Navigator field unit.



## Calibrated leak

A Calibrated leak is one that was created specifically for the purpose of calibrating devices with the antennas, cables, filters, and combiners used in the vehicle. Calibration locations are shown with a green flag.



## Show tech location



By selecting the show technician location box, the current location of each technician will be displayed on the map. Technician can be selected via pulldown.

Order/leak type: Technician ID: From: To: Leak level >= QAM band/channel: Hub ID: ☐ Show tech location ☐ Load and show node boundary



All All 9/17/2013 11/ 8/2013 All All All

☒ Show tech location (4:34:20 PM)

All

## Google view -satellite

After right clicking on any leak, press the Google button and a Google map will be displayed.



An alternative method is to right click on any leak in the database, and click on Satellite

31m 103ft


Order: All To: 3/29/2012 Leak level >=: All QAM channel: All Hub ID: All ☐ Show tech location

Leak level [µV/m]	Lat	Lon	Address	Hub	Node	Repaired date
708	43.01	-76.13	130 Game Rd		Not available	
562	43.01	-76.13	136 Game Rd		Not available	
501	43.00	-76.13	958 E Brighton Ave	Local hub	Not available	
501	43.01	-76.13	132 Game Rd	Local hub	Not available	

Context menu options: Accept work order, Close work order, Edit work order, Restore selected leak as actual, Remove leak from list, Satellite (highlighted with red arrow)


## Remove leak from list

In order to remove a leak from the database, select the desired leak by right clicking. You will be asked to confirm that you do want to delete this leak, and then you will be required to enter the password to delete it.





## Remove group of leaks

In order to remove a group of leak from the database, right click on Remove group of leaks text.




After the rights confirmation you will be prompted to select the criterion upon which to remove leaks. Date range and leak levels can be selected.




## Edit a work order – reassign to a different technician

To reassign an existing open work order to a different technician, right click on the desired open work order.




Then select a different technician from the dropdown list and it will be reassigned, a confirming email will be sent if the email box is checked.



## Close a work order from Manager Program

To close a work order, right click on it and select Close work order. Add technician information and close code and confirm.




Close work order  
Edit work order  
Setup calibrated leak  
Restore selected leak  
Remove leak from list  
Remove group of leaks

Leak ID	Detected date	Work Order Date	Work Order Tech ID	Leak level [μV/m]	LTE level [dBm]	Address	PSID	Hub	Node	Repaired date
181	9/17/2013	12/4/2013	Ggsm2	794	-60	287 Ainsley Dr, Syracuse		syracuse2		
182	9/17/2013	12/4/2013	Ggsm2	355		Ainsley Dr, Syracuse		syracuse2		
185	9/17/2013	12/4/2013	Ggsm2	40	-66	349 Ainsley Dr, Syracuse		syracuse2		
197	11/20/2013	12/4/2013	Ggsm2	447		148 Game Rd, Syracuse		syracuse2		
205	12/3/2013	12/4/2013	Ggsm2	282	-89	287 Ainsley Dr, Syracuse		syracuse2		

## Undo a previously closed leak


If a leak was closed in error, it can un-done. From the listing of Closed orders, right click and press restore selected leak.



Close work order  
Edit work order  
Setup calibrated leak  
Restore selected leak  
Remove leak from list  
Remove group of leaks

Leak ID	Detected date	Work Order Date	Work Order Tech ID	Leak level [μV/m]	LTE level [dBm]	Address	PSID	Hub	Node	Repaired date	Comment
897	1/21/2013	11/10/2013	5715	200		23763 Mastick Rd		WOW Cleve.	North Olmsted	11/11/2013	No leak. 10.Replaced Passive Device
1143	2/5/2013	11/10/2013	5715	112		4953 Columbia Rd North Olmsted		WOW Cleve.	North Olmsted	11/11/2013	No leak. 03.Loose Faceplate
2136	5/9/2013	11/10/2013	5715	112		23948 Lorain Ave North Olmsted		WOW Cleve.	North Olmsted	11/12/2013	No leak. 10.Replaced Passive Device
1120	2/4/2013	11/10/2013	5715	158		23915 Lorain Ave North Olmsted		WOW Cleve.	North Olmsted	11/12/2013	No leak. 26.Broken Tap Port
1870	4/5/2013	11/13/2013	5713	22		4044 Lowden Rd South Euclid		WOW Cleve.	South Euclid	11/13/2013	No leak. 27.Damaged Hardline

After confirming, it will be considered an unassigned leak, with the comment that it was restored.



Order type: Technician ID: From: To: Leak level >=: QAM channel: Hub ID: Show tech location


Unassigned All 12/ 9/2011 3/29/2012 All All All

Leakage table - unassigned leaks (89 total)

Leak ID	Detected date	Work Order Date	Work Order Tech ID	Leak level [μV/m]	Lat	Lon	Address	Hub	Node	Repaired date	Comment
1	12/9/2011			501	43.01	-76.13	130 Game Rd	Local hub	Not available		Restored from fixed


## Calculate leak at point

The software contains a useful utility that has the ability to show the leak level at any location. Move the mouse to any location on the map and right click, the select Calculate leak at point. An information box appears that shows the leak level at the desired location that is resultant from the existing leaks in the







database. The three lines of information correspond to the three configured detection bands. In the example to the right leakage was only being monitored at the high frequency band.



## Setup Calibrated leak

Calibrated leak locations can be created that can allow for automatic device calibration. Leak setup should only be performed by a technician familiar with the calibration process and calibration instruction provided by Arcom. After the calibrated leak is recorded in the database at the desired location, the status of the leak is changed from Unassigned to Calibrated. A dialog box will appear asking if the leak status should be changed. Only Global QAM channels can be calibrated.




## File

The File menu item provides alternative access to Connect to server, and it provides




the ability to Print and Save screens, and to exit the program. Additionally it allows the user to view and simulate previously stored drive routes and to use a tool for calculating the value of calibrated leaks.



### View downloaded driving routes


Any driving routes that have been previously downloaded onto the PC running the Manager program can be viewed again by selecting View downloaded driving routes from the File menu.

Navigate to the QAM Snare folder in Documents – this folder was created during the program installation process. The driving route will then be displayed.




### Simulate downloaded driving routes


Previously downloaded driving routes can be viewed and reproduced point by point. After confirming yes, navigate to the QAM Snare Manager folder where the driving traces are stored (this folder was created upon setup). Then further navigate to the desired Device ID and select the QAM Snare trace file from the list.



The user can select which of the data points to start running the simulation. Press the right arrow to start the simulation, the pause button to pause, and the red downward arrow to reset.



The moving drive path is indicated as shown below, data points are continually added.




Right clicking on any of the drive path points will provide information on what was detected at that specific point as shown below.

1/30/2012 1:08:36 PM
#: 7791
Level: 56.2 µV/m
Delay: 20.47 µs
Hub: 0/ Google

## Calibrated leak calculator

The calibrated leak calculator is a tool that is used to help determine the characteristics of a calibrated leak when using an antenna with a known gain. Enter the QAM signal level, antenna gain at desired frequency, and the distance to the receive antenna – and the calibrated leak field strength can be determined. Differences between this number and the number that the Navigator or Monitor measures can be used to calculate calibration coefficients for the field device.

**Calibrated leak calculator**



Leak source calibrated biconical vertical oriented antenna

D = 30...60 feet  
10...20 meters

12...20 feet  
4...6 meters

Tap

QAM signal level at leak antenna input, [dBmV]:

Leak antenna gain at selected QAM channel, [dBi]:

Distance to leak antenna D [m]:

Calculate


**Calibrated leak field strength [μV/m]:**

Close

## Database

The database menu item provides alternative access to Driving routes and the Work order and leak database. It also provides access to the Server audit, and


provides a way to view node and PSID boundaries on the maps. It additionally provides a way to Edit Hub/Node boundaries.



## Server audit

QAM Snare contains many audit features that can monitor activity associated with the database.

After the Server audit button is pressed the Server audit window opens.



**Server audit**

From: 24.11.2012 To: 28.11.2012 Get audit data

N	Server login	Connect	Disconnect	Host	Host login	Client IP	External IP
69	ADMIN	27.11.2012 6:04:10	27.11.2012 6:04:29	ANTON	User	192.168.1.18	192.168.1.1
70	ADMIN	27.11.2012 6:06:33	27.11.2012 6:07:32	ANTON	User	192.168.1.18	192.168.1.1
71	ADMIN	27.11.2012 6:07:58	27.11.2012 6:16:47	ZINEVICH3	Victor	192.168.1.122	192.168.1.1
72	ADMIN	27.11.2012 23:56:03	27.11.2012 23:57:33	SPK13	Hohmasoft	192.168.1.2	192.168.1.1
73	ADMIN	28.11.2012 0:21:32	28.11.2012 0:22:39	ANTON	User	192.168.1.18	192.168.1.1
74	ADMIN	28.11.2012 1:18:05	28.11.2012 1:18:47	ANTON	User	192.168.1.18	192.168.1.1
75	ADMIN	28.11.2012 1:22:23	28.11.2012 1:23:36	ANTON	User	192.168.1.18	192.168.1.1
76	ADMIN	28.11.2012 1:27:06	28.11.2012 1:33:41	SPK13	Hohmasoft	192.168.1.2	192.168.1.1
77	ADMIN	28.11.2012 1:50:24	28.11.2012 1:52:08	ANTON	User	192.168.1.18	192.168.1.1
78	ADMIN	28.11.2012 1:57:25	28.11.2012 1:58:25	ZINEVICH3	Victor	192.168.1.122	192.168.1.1
79	ADMIN	28.11.2012 2:09:42		SPK13	Hohmasoft	192.168.1.2	192.168.1.1
80	ADMIN	28.11.2012 2:26:31	28.11.2012 2:29:51	ANTON	User	192.168.1.18	192.168.1.1

Current user: ADMIN [192.168.1.18] Manager 6.0.5.2  
Current host: ANTON (User)

Date	Audit info
28.11.2012 1:50:39	Setup/change list of technician. Dropped technician Device = qqqqq89, Technician = TestQAM89
28.11.2012 1:50:42	Setup/change list of technician. Dropped technician Device = qqqqq12, Technician = TestQAM12
28.11.2012 1:50:54	Setup/change list of technician. Updated technician Device = qqqqq13, Technician = TestQAM13
28.11.2012 1:50:57	Setup/change list of technician. Dropped technician Device = qqqqq10, Technician = TestQAM10
28.11.2012 1:51:17	Setup/change list of technician. Added technician Device = , Technician = new1
28.11.2012 1:51:20	Setup/change list of technician. Dropped technician Device = qqqqq17, Technician = TestQAM17

Print current user Info Close

To access audit data, first enter the date range and press get Audit data.

From: 24.11.2012 To: 28.11.2012 Get audit data



Pressing on any of the Server logins will display information related to the sign-on, and software version of the QAM Snare Manager.

Current user:	ADMIN [192.168.1.18] Manager 6.0.5.2
Current host:	ANTON (User)


Information on what the particular user did during the session will be displayed on the lower window. If no database actions occurred then the lower portion of the screen will be blank.

Date	Audit info
28.11.2012 1:50:39	Setup/change list of technician. Dropped technician Device = qqqqq89, Technician = TestQAM89
28.11.2012 1:50:42	Setup/change list of technician. Dropped technician Device = qqqqq12, Technician = TestQAM12
28.11.2012 1:50:54	Setup/change list of technician. Updated technician Device = qqqqq13, Technician = TestQAM13
28.11.2012 1:50:57	Setup/change list of technician. Dropped technician Device = qqqqq10, Technician = TestQAM10
28.11.2012 1:51:17	Setup/change list of technician. Added technician Device = , Technician = new1
28.11.2012 1:51:20	Setup/change list of technician. Dropped technician Device = qqqqq17, Technician = TestQAM17

### Load and show node boundary


To display node boundaries, click on the Load and show node boundary text, or press the displayed hot key sequence. Node boundaries will be displayed. When you hover over a node with your mouse, the node ID will be displayed. If node boundaries do not exist, then the Load and show node boundary line will not be displayed.

Database	Reports	Help
Driving routes		Ctrl+F7
Work order/leak database		Ctrl+F8
Server audit		Ctrl+F9
<input checked="" type="checkbox"/> Load and show node boundary		Shift+Ctrl+F7
<input checked="" type="checkbox"/> Load and show PSID boundary		Shift+Ctrl+F8
Edit Hub boundaries		Ctrl+F10



## Load and show PSID boundary

To display PSID boundaries, click on the Load and show PSID boundary text or press the displayed hot key sequence. The PSID number will be displayed when you hover over an area with your mouse.





## Edit Hub/Node boundaries


**Hub** and node boundaries can be configured by Arcom Digital if electronic maps are supplied. Additionally, hub and node boundaries can be manually changed.

After clicking on the Edit Hub/Node boundaries button, a Warning message will appear, indicating that if not done properly, that the database may become corrupt and that it could affect the multi hub operating mode. If you want to continue, press yes – if you are unsure as to the process press No and contact your Arcom Digital representative for guidance.


After answering yes, the existing hubs and node map will open in edit mode, with all the boundary inflection points highlighted with a red square.




Right click on the desired point to want to change and a menu item appears.




When the task is completed and the changes are made, you need to exit Edit mode. Click Database – Close edit Hub/Node boundaries.




A Confirm Window will appear asking if you wish to save changes.




To change existing boundaries, after entering the edit mode, go to the map location where you wish to make changes, and right click to access the Edit menu items, and select the desired task.



When you select Add point, a new data point in the form of a red box will be created midpoint adjacent to the selected line and data point. This new data point can be dragged to the desired position. This process can be repeated until the boundary is of the desired shape in the desired location.




To create a Hub boundary at the cursor location, click Create Hub boundary. You will be asked for the Hub ID which must be selected from the list. If the Hub name is not present, it must be first created in Settings – List of Hubs.






After adding the hub boundaries, and creating the desired shape by adding data point and dragging to the desired location, you need to save the changes. This is accomplished by going into Database – close Edit Hub/Node boundaries.




And Confirming that you want to Save the changes.




## Reports

QAM Snare provides many useful reporting features, the capabilities of which will be expanded over time.




### CLI report


To create a CLI report, press Create report.



A window will appear asking if you want to create a new report.




And then it will request the time range and the CLI report ID which is selectable from the drop down list. The name of the report is configured in Settings – List of Hubs.



## Leak statistics

**Summary statistics** – provides information by hub for a given date range, for the number of leaks in each band and level. Leak information is provided as to the number of detected leaks, and the number of leaks that are actionable. An actionable leak is one that according to parameters established in Work Orders, needs to be fixed.



The screenshot shows the 'Leak statistics' window with the 'Summary statistics' tab selected. The date range is set from 9/10/2012 to 9/12/2012. The interface displays two tables of data.

Parameter	Frequency band	Syracuse2	Syracuse1	Syracuse3	Total
<b>Leaks (Detected/Actionable)</b>	Low	5/5	9/6	10/4	24/15
	Middle	0/0	0/0	0/0	0/0
	High	5/5	1/1	0/0	6/6
	Total:	6/6	9/6	10/4	25/16
<b>Leak level, <math>\mu\text{V}/\text{m}</math> (AVG/MAX)</b>	Low	86/177	62/199	30/79	59/376
	Middle	0/0	0/0	0/0	0/0
	High	119/316	63/63	0/0	61/316
	AVG/MAX:	68/316	42/199	10/79	120/376

At the bottom of the window, there are buttons for 'Print report', 'Save report', and 'Close'.




**Leak statistics over time interval**– displays the number of detected and actionable leaks by Day, Week, Month, or Quarter for any Date range. It is a good way to look at trends.

The screenshot shows a software window titled "Leak statistics". It has three tabs: "Summary statistics", "Leak statistics over time interval" (which is selected), and "Leak charts". Below the tabs, there is a date range selector showing "from 9/10/2012 to 9/16/2012" and a time interval selector with options "Day", "Week" (selected), "Month", and "Quarter". An "Update" button is to the right. The main area contains a table with the following data:

Hub ID	Frequency band	week 37
Syracuse2	Low	5/5
	Middle	0/0
	High	5/5
	Total leaks: (Detected/Actionable)	6/6
Syracuse1	Low	9/6
	Middle	0/0
	High	1/1
	Total leaks: (Detected/Actionable)	9/6
Syracuse3	Low	10/4
	Middle	0/0
	High	0/0
	Total leaks: (Detected/Actionable)	10/4


At the bottom of the window, there are buttons for "Print report", "Save report", and a "Close" button.

**Leak charts**– enter date range, press on Detected to toggle to Actionable, press Hub ID, check hubs you would like to see charts on – and press update



## Driving route reports



**Summary Statistics** – Provides the number of miles driven for each field device, by Day, Week, Month, or Quarter– within a selected date range. For each Tech ID it also provides information as to the number of (Detected/Actionable/Repaired) leaks for the selected period.


Driving route reports

Summary statistics
Hub coverage

Date range: from  to 
Time interval:

N	Tech ID	Level	Device	9/13/2012	Total
1	555(2)		Navigator	0 ml 0/0/0	0 ml 0/0/0
2	12345(3)		Navigator	10 ml 7/7/0	10 ml 7/7/0
3	400(4)		Navigator	20 ml 12/12/0	20 ml 12/12/0
4	arcom(6)		Navigator	0 ml 1/1/0	0 ml 1/1/0
			<b>TOTAL miles (Detected/Actionable/Repaired)</b>	<b>30 ml 16/16/0</b>	<b>30 ml 16/16/0</b>

 Print report
 Save report
Close



**Hub Coverage** – shows the percentage of total miles driven versus the total number of hub miles. The hub miles number comes from the value entered in System settings–list of hub–plant miles for the hub.

Driving route reports

Summary statistics | Hub coverage

Date range: from 9/12/2012 to 9/14/2012 Time interval: Day Week Month Quarter **Update**

N	Hub ID	9/12/2012	9/13/2012	9/14/2012	9/15/2012	9/16/2012	TOTAL
1	Syracuse1	41164 ml/17%	41164 ml/18%	41164 ml/19%	41164 ml/20%	41164 ml/21%	41164 ml/16%
2	Syracuse2	41664 ml/18%	41664 ml/19%	41664 ml/20%	41664 ml/21%	41664 ml/22%	41664 ml/17%
3	Syracuse3	42164 ml/19%	42164 ml/20%	42164 ml/21%	42164 ml/22%	42164 ml/23%	42164 ml/18%
4	TOTAL:	42664 ml/20%	42664 ml/21%	42664 ml/22%	42664 ml/23%	42664 ml/24%	42664 ml/19%

Print report Save report Close

## Repair reports

**Summary repair statistics**– Provides high level information on leaks repaired (closed) by hub for a given date range. Includes the number of repaired leaks, repair time, and repair level. Enter desired date range and press Update.

Summary repair statistics				Repair statistics over time interval	Repair charts
Date range: from 01.11.2012 to 28.11.2012				Update	
Parameter	Frequency band	Local hub	Total		
Repaired leaks	Low	0/0%	0/0%		
	Middle	0/0%	0/0%		
	High	18/100%	18/100%		
	Total:	18	18		
Repaired time, days (AVG/MAX/MIN)	Low	0/0/0	0/0/0		
	Middle	0/0/0	0/0/0		
	High	4/13/1	4/13/1		
	Total:	4/13/1	4/13/1		
Repaired leak level, $\mu\text{V/m}$ (AVG/MAX/MIN)	Low	0/0/0	0/0/0		
	Middle	0/0/0	0/0/0		
	High	112/282/9	112/282/9		
	Total:	112/282/9	112/282/9		

**Repair statistics over time interval** – shows the number of leaks repaired over a time interval.

Summary repair statistics

Repair statistics over time interval

Repair charts


Date range: from 01.11.2012 to 28.11.2012

Time interval: Day Week Month Quarter


Update

Hub ID	Frequency band	09.11.2012	16.11.2012	19.11.2012	20.11.2012	21.11.2012	
Local hub	Low	0	0	0	0	0	
	Middle	0	0	0	0	0	
	High	2	4	3	7	2	
	Total leaks:	2	4	3	7	2	


**Repair charts** – provides a graphical representation of various leakage parameters.



First select the desired date range. Then select the type of chart from the drop down list.



Click on the work "Hub ID", and a Hub selection window will appear.




After making selection of Hub(s), press OK, and then press Update to update the chart. The Y-scale can be adjusted by moving the slide cursor at the bottom of the graph.

## Technicians productivity

The Technicians productivity report provides information as to what technicians are doing in the field. It shows miles driven, new miles driven, the number of detected and actionable leaks, and the number of work orders assigned and repaired.

[illegible]

First select the date range and then click on the wording “Tech ID” to open the Select technician window.




After selecting the desired technician press OK, then Update.

**Update**

## Server Statistics

Server Statistics provides information on performance of the server. When selecting the date range, **a maximum of 10 days of data can be displayed**. After selecting the desired date range press the Update button. The top 1/3 of the report shows the number of Navigators or Monitors that connected to the server. The middle third shows the average and max data delivery time from server to the field unit. The bottom 1/3 shows the percent of data successfully delivered from the server to the field unit as well as the leak calculation % which is a relative indication of how much of the computer resources are being utilized.



## Device Calibration

Device calibration provides a report showing last calibration date and when the next calibration is due for each device contained in List of Devices. The calibration due date can be changed in System Settings – Leak Detector – Device Calibration.

Device calibration (period 6 months)

#	Device ID	Technician ID	Last calibration date	Next calibration date	Status
1	Administrator		4/9/2013	10/9/2013	Alarm
2	arcom	arcomMonitorX2	4/9/2013	10/9/2013	Alarm
3	arcomMonitor	arcomMonitor	5/30/2013	11/30/2013	OK
4	arcomMonitorX	arcomMonitorX	10/25/2013	4/25/2014	OK
5	Arcomb	Arcomb	7/3/2013	1/3/2014	OK
6	arcomMonitorX1	arcomMonitorX1	10/11/2013	4/11/2014	OK
7	Arcom	Arcom	11/8/2013	5/8/2014	OK
8	arcom	arcomMonitor3	8/14/2013	2/14/2014	OK
9	ddeyo	TEMPTESTS	8/15/2013	2/15/2014	OK
10	4426	Rob	8/15/2013	2/15/2014	OK
11	CablevisionTEST	CablevisionTEST	10/8/2013	4/8/2014	OK
12	G	00069	8/20/2013	2/20/2014	OK
13	G	arcomMonitorG	10/9/2013	4/9/2014	OK
14	G	00040	8/21/2013	2/21/2014	OK
15	ArcomSB	00318	8/23/2013	2/23/2014	OK
16	G	Rev07	8/29/2013	2/28/2014	OK
17	22222	c1m	9/5/2013	3/5/2014	OK
18	Arcom	00684	9/8/2013	3/8/2014	OK
19	Arcom	00675	9/8/2013	3/8/2014	OK
20	RX	ArcomRX	9/8/2013	3/8/2014	OK
21	ArcomGSM	00689	9/11/2013	3/11/2014	OK
22	Arcom	00088	9/12/2013	3/12/2014	OK
23	Arcom	ArcomGSM	9/17/2013	3/17/2014	OK
24	Arcom	ArcomWIFI	9/17/2013	3/17/2014	OK

Print report Export data Close

## Export Data

The export data application provides an easy method to port data to other applications. Select the date range and press the Export data button.

Export data

Date range  
from 12/ 1/2012 to 12/12/2012


Export parameters  
☒ Export driving route summary ☒ Export driving routes  
☒ Export all leaks from period

Additional leak properties  
☐ Resolve physical address ☒ Enable store Lat/Lon  
☐ Check node boundaries


Start export data Close




You will see those files that are being exported, and will receive a confirmation message when the export is complete.



Data is stored in the QAM Snare Directory in Documents/Export/Server name/Date. Format is .CSV which excel can easily parse.



## Help




## Program help

Program help is available by pressing F1 on any screen.



## Color indicator

A pallet showing colors used for leak indication is shown here.




## About


About provides information on the software version and license.



## Print work order

Work orders and information on detected leaks can be printed by clicking on the Print work order button at the bottom right of the screen.





User has the option of printing the selected work order or all work orders.

